COUPLINGS AND FITTINGS

Fittings

Flexible couplings to isolate the pump, and brass and polypropylene fittings from ½" to 2".

Stainless flexible couplings

- **Quieter installs.** Stops pump vibration travelling down the pipework.
- **No kinks.** Corrugated HDPE core bends tight without collapsing.
- **Built to last.** AISI 304 stainless braid and sleeves, brass ends.
- **Drinking-water approved.** Fitted by hand, no tools.



Size	Hose I.D.	Hose O.D.	Min. bend radius	Pressure	Max. temp.
½"	16 mm	22 mm	—	10 bar	70 °C
¾"	19 mm	25 mm	35 mm	10 bar	70 °C
1"	26 mm	32 mm	45 mm	10 bar	70 °C
1¼"	32.5 mm	40 mm	60 mm	10 bar	70 °C
1½"	36 mm	44 mm	70 mm	10 bar	90 °C
2"	48 mm	55 mm	100 mm	10 bar	90 °C

Brass and polypropylene fittings



Brass fittings EN 1982 brass · ½" to 2" · drinking-water safe

Nipple · Reducing nipple · Socket · Reducing bush · Elbow MF · Elbow FF · Tee · Union MF · Union FF · Cap



Blue-pipe compression Polypropylene · 19 mm × ½" to 63 mm × 2"

Straight · Male adaptor · Female adaptor · Elbow · Male elbow · Female elbow · Tee · Ball valve



Threaded polypropylene Impact resistant · ½" to 2"

Nipple · Reducing nipple · Socket · Reducing socket · Reducing bush · Elbow MF · Elbow FF · Tee