ALPHA · 80 µm

Inline sediment filter

Fit it ahead of pumps, softeners and UV sterilisers. It traps sand, rust and silt before they reach the equipment downstream.

Key features

- **Two gauges.** Inlet and outlet pressure side by side, so you can see when the cartridge needs cleaning.
- **Washable cartridge.** The 80 µm cartridge rinses clean and goes back in.
- **Standard 5" size.** Takes standard 5" replacement cartridges.
- **Easy to service.** Built-in drain point, with an opening spanner supplied.
- **Compact.** Fits where space is tight.



Where it fits Water supply → **ALPHA filter** → Pump, softener or UV

Specification

Model	**ALPHA**
Connections	**1"**
Filtration	**80 µm**
Cartridge	**5", washable**
Gauges	**Inlet and outlet**
Max. working pressure	**10 bar**
Water temperature	**+5 to +45 °C**
Ambient temperature	**+5 to +55 °C**
Weight	**1.5 kg**

Installation & operation

Fit it upstream of the equipment it protects, with the arrow on the body in the direction of flow.

Clean the cartridge when the outlet gauge reads noticeably lower than the inlet.

Isolate the supply and release the pressure before opening the filter.

Spare 5" cartridges available from stock.

Protecting a softener or UV?
Tell us your system and we'll put the treatment in the right order.

+353 1 456 4099