10" AND 20" · STANDARD AND JUMBO

Water filter housings

Fit one upstream of the pump or the house supply. It catches sand, grit and rust before they reach impellers, seals and valves.



10" Standard



10" Double



10" Jumbo



20" Standard



20" Jumbo

Models

Housing	Stages	Cartridge	Ports	Max. flow	Best for
10" Standard	1	2.5" × 10"	¾" brass	40 l/min	Whole-house, mains
10" Double	2	2 × 2.5" × 10"	¾" brass	40 l/min	Sediment, then carbon
10" Jumbo	1	4.5" × 10"	1" brass	58 l/min	Wells and boreholes
20" Standard	1	2.5" × 20"	1" brass	58 l/min	Higher demand, slim fit
20" Jumbo	1	4.5" × 20"	1" brass	58 l/min	Heavy sediment loads

Flow without cartridge. Blue or clear bowls; a clear bowl shows when the cartridge needs changing.

Cartridges

Cotton threaded
Sediment: sand, grit and rust

PP sediment
Sediment: fine suspended particles

Block carbon
Chlorine, taste and odour

Every housing takes all three, in its own size.

Installation & operation

Seal threads with PTFE tape only, never paste or hemp.

Press the relief button to release pressure before opening the bowl.

Keep away from heat sources, or fit a non-return valve.

Max. pressure
7 bar at 20 °C

Max. temperature
40 °C

Limits for the 10" and 20" standard housings.